

Brtvena pletenica tip 2026

Sastav materijala:

Brtvena pletenica dijagonalnog pletenja, proizvedena od teksturalnog staklenog vlakna, potpuno impregnirana teflonskom disperzijom i sa startnim (break-in) lubrikantom bez silikona.

Osobine:

Brtvena pletenica visoke gustoće, gipka i fleksibilna, sa dobrom kemijskom otpornošću.

Područja primjene:

TEADIT 2026 se preporučuje za brtvljenje centrifugalnih i klipnih pumpi, ventila, mješača, agitatora itd., u naftnoj, prehrambenoj i kemijskoj industriji, šećeranama, postrojenjima za preradu vode, industriji celuloze i papira.

Fluidi:

TEADIT 2026 se koristi za brtvljenje vode, pare, kemikalija, otapala, ulja, blažih kiselina i baza itd.



Prednosti:

Tip 2026 je multi-funkcionalna brtvena pletenica, koja se može koristiti u raznim aplikacijama unutar jednog postrojenja.

Ne koristi se za:

Koncentrirane kiseline i baze, kisik.

Temperatura: - temp.: + temp.:
(°C) 40 280

Tlak: rotacioni: recipročni: statički:
(bar) 15 20 150

pH: 3-12

Gustoća:(g/cm³) 2

Brzina na vratilu:
(m/s) 8

TEADIT INTERNATIONAL PRODUKTIONS GMBH

Rosenheimer Str.10 Tel.: +43 - 5372 - 64020 - 0
A-6330 Kufstein Fax: +43 - 5372 - 64020 - 20
e-mail: mail@teadit-europe.com

TEADIT ITALIA S.p.A.

Via Vanzago 13 Tel.: +39 - 035 - 924911
I-25030 Paratico Fax: +39 - 035 - 913060
e-mail: sales@teadit.it

Since all properties, specifications and application parameters shown throughout this product information are approximate and may be mutually influenced, your specific application should not be undertaken without independent study and evaluation for suitability. All technical data and advice given is based on experiences TEADIT has made so far. Failure to select proper sealing products can result in damage and/or personal injury. Properties, specifications and application parameters are subject to change without notice. TEADIT does not undertake liability of any kind whatsoever.

The power of elements

